

■ブーム

単位 (t)

アウトリガ最大張出 (6.0m) ー 全 周 ー						
ブーム長さ 作業半径	7.0m	11.7m	16.4m	21.1m	25.8m	30.5m
2.5m	20.0	12.0	12.0	9.0		
3.0m	20.0	12.0	12.0	9.0		
3.5m	20.0	12.0	12.0	9.0	7.0	
4.0m	18.5	12.0	12.0	9.0	7.0	
4.5m	16.5	12.0	12.0	9.0	7.0	5.0
5.0m	14.2	12.0	12.0	9.0	7.0	5.0
5.5m		12.0	11.9	9.0	7.0	5.0
6.0m		12.0	11.1	9.0	7.0	5.0
6.5m		11.3	10.35	8.5	7.0	5.0
7.0m		10.0	9.7	8.1	6.65	5.0
8.0m		7.85	7.45	7.2	5.95	4.65
9.0m		6.3	5.9	6.4	5.3	4.2
10.0m			4.75	5.2	4.75	3.8
11.0m			3.9	4.35	4.3	3.45
12.0m			3.2	3.65	3.85	3.15
13.0m			2.7	3.1	3.35	2.9
14.0m			2.25	2.65	2.9	2.65
15.0m				2.25	2.5	2.45
16.0m				1.9	2.15	2.25
17.0m				1.6	1.85	2.0
18.0m				1.35	1.6	1.75
19.0m				1.15	1.4	1.55
20.0m					1.2	1.35
22.0m					0.9	1.05
24.0m					0.75	0.8
26.0m					(23.0m)	0.55
28.0m						0.4
A (°)	0~82					

A: ブーム角度の範囲 (無負荷時)

単位 (t)

アウトリガ中間張出 (5.6m) ー 側 方 ー						
ブーム長さ 作業半径	7.0m	11.7m	16.4m	21.1m	25.8m	30.5m
2.5m	20.0	12.0	12.0	9.0		
3.0m	20.0	12.0	12.0	9.0		
3.5m	20.0	12.0	12.0	9.0	7.0	
4.0m	18.5	12.0	12.0	9.0	7.0	
4.5m	16.5	12.0	12.0	9.0	7.0	5.0
5.0m	14.2	12.0	12.0	9.0	7.0	5.0
5.5m		12.0	11.9	9.0	7.0	5.0
6.0m		12.0	11.1	9.0	7.0	5.0
6.5m		10.3	10.1	8.5	7.0	5.0
7.0m		8.9	8.8	8.1	6.65	5.0
8.0m		6.9	6.75	7.2	5.95	4.65
9.0m		5.5	5.35	5.8	5.3	4.2
10.0m			4.3	4.75	4.75	3.8
11.0m			3.5	3.95	4.15	3.45
12.0m			2.9	3.3	3.6	3.15
13.0m			2.35	2.75	3.05	2.9
14.0m			1.95	2.3	2.6	2.65
15.0m				1.95	2.25	2.35
16.0m				1.65	1.9	2.1
17.0m				1.4	1.65	1.8
18.0m				1.15	1.4	1.55
19.0m				1.0	1.2	1.35
20.0m					1.0	1.15
22.0m					0.7	0.85
24.0m					0.6	0.6
26.0m					(23.0m)	0.4
A (°)	0~82					26~82

A: ブーム角度の範囲 (無負荷時)

単位 (t)

アウトリガ中間張出 (4.7m) ー 側 方 ー						
ブーム長さ 作業半径	7.0m	11.7m	16.4m	21.1m	25.8m	30.5m
2.5m	20.0	12.0	12.0	9.0		
3.0m	20.0	12.0	12.0	9.0		
3.5m	20.0	12.0	12.0	9.0	7.0	
4.0m	18.5	12.0	12.0	9.0	7.0	
4.5m	16.5	12.0	12.0	9.0	7.0	5.0
5.0m	13.0	12.0	12.0	9.0	7.0	5.0
5.5m		10.4	10.2	9.0	7.0	5.0
6.0m		8.8	8.7	9.0	7.0	5.0
6.5m		7.5	7.35	7.9	7.0	5.0
7.0m		6.5	6.4	6.9	6.65	5.0
8.0m		5.05	4.85	5.4	5.55	4.65
9.0m		3.95	3.8	4.3	4.55	4.2
10.0m			3.0	3.45	3.75	3.8
11.0m			2.4	2.8	3.15	3.25
12.0m			1.9	2.3	2.6	2.75
13.0m			1.5	1.9	2.2	2.35
14.0m			1.15	1.55	1.8	1.95
15.0m				1.25	1.5	1.65
16.0m				1.0	1.25	1.4
17.0m				0.8	1.05	1.2
18.0m				0.6	0.85	1.0
19.0m				0.45	0.65	0.8
20.0m					0.5	0.65
22.0m						0.4
A (°)	0~82			34~82	40~82	

A: ブーム角度の範囲 (無負荷時)

単位 (t)

アウトリガ最小張出 (3.6m) ー 側 方 ー						
ブーム長さ 作業半径	7.0m	11.7m	16.4m	21.1m	25.8m	30.5m
2.5m	20.0	12.0	12.0	9.0		
3.0m	20.0	12.0	12.0	9.0		
3.5m	16.0	12.0	12.0	9.0	7.0	
4.0m	12.3	12.0	11.7	9.0	7.0	
4.5m	9.8	9.6	9.4	9.0	7.0	5.0
5.0m	7.7	7.8	7.65	8.0	7.0	5.0
5.5m		6.5	6.3	6.8	7.0	5.0
6.0m		5.5	5.35	5.85	6.2	5.0
6.5m		4.7	4.6	5.05	5.35	5.0
7.0m		4.1	3.95	4.4	4.7	4.7
8.0m		3.1	3.0	3.4	3.7	3.85
9.0m		2.35	2.25	2.65	2.95	3.1
10.0m			1.7	2.05	2.35	2.5
11.0m			1.2	1.6	1.85	2.0
12.0m			0.8	1.25	1.45	1.65
13.0m			0.5	0.95	1.15	1.35
14.0m				0.65	0.9	1.05
15.0m				0.45	0.7	0.85
16.0m					0.5	0.65
17.0m						0.5
A (°)	0~82		26~82	39~82	48~82	54~82

A: ブーム角度の範囲 (無負荷時)

ブーム・ジブ

■ジブ

アウトリガ最大張出 (6.0m) ー 全 周 ー						
ジブ長さ	30.5mブーム+3.8mジブ					
オフセット	5°		25°		45°	
ブーム 角度	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)
82°	4.4	3.0	6.0	2.0	6.9	1.4
80°	5.6	3.0	7.2	2.0	8.1	1.4
75°	8.6	3.0	10.3	2.0	11.1	1.4
73°	9.8	2.6	11.4	2.0	12.2	1.4
70°	11.4	2.3	13.2	1.9	13.8	1.37
65°	14.1	1.85	15.8	1.65	16.4	1.33
60°	16.7	1.5	18.3	1.4	18.9	1.3
55°	19.1	1.25	20.6	1.2	21.1	1.15
50°	21.5	1.05	22.8	1.0	23.1	1.0
45°	23.5	0.75	24.7	0.75	25.0	0.75
40°	25.4	0.55	26.4	0.55		
35°	27.1	0.4	27.9	0.4		
A(°)	34~82			44~82		

A: ブーム角度の範囲(無負荷時)

アウトリガ中間張出 (5.6m) ー 側 方 ー						
ジブ長さ	30.5mブーム+3.8mジブ					
オフセット	5°		25°		45°	
ブーム 角度	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)
82°	4.4	3.0	6.0	2.0	6.9	1.4
80°	5.6	3.0	7.2	2.0	8.1	1.4
75°	8.6	3.0	10.3	2.0	11.1	1.4
73°	9.8	2.6	11.4	2.0	12.2	1.4
70°	11.4	2.3	13.2	1.9	13.8	1.37
65°	14.1	1.85	15.8	1.65	16.4	1.33
60°	16.7	1.5	18.3	1.4	18.9	1.3
55°	19.1	1.2	20.6	1.15	21.1	1.15
50°	21.4	0.85	22.7	0.85	23.1	0.85
45°	23.5	0.6	24.7	0.6	24.9	0.6
40°	25.4	0.4	26.4	0.4		
A(°)	39~82				44~82	

A: ブーム角度の範囲(無負荷時)

アウトリガ中間張出 (4.7m) ー 側 方 ー						
ジブ長さ	30.5mブーム+3.8mジブ					
オフセット	5°		25°		45°	
ブーム 角度	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)
82°	4.4	3.0	6.0	2.0	6.9	1.4
80°	5.6	3.0	7.2	2.0	8.1	1.4
75°	8.6	3.0	10.3	2.0	11.1	1.4
73°	9.8	2.6	11.4	2.0	12.2	1.4
70°	11.4	2.3	13.2	1.9	13.8	1.37
65°	14.1	1.75	15.8	1.65	16.4	1.33
60°	16.7	1.15	18.2	1.15	18.8	1.05
55°	19.1	0.75	20.5	0.75	21.0	0.7
50°	21.4	0.45	22.6	0.45	23.0	0.45
A(°)	49~82					

A: ブーム角度の範囲(無負荷時)

アウトリガ最小張出 (3.6m) ー 側 方 ー						
ジブ長さ	30.5mブーム+3.8mジブ					
オフセット	5°		25°		45°	
ブーム 角度	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)	作業半径 (m)	定 格 総荷重 (t)
82°	4.4	3.0	6.0	2.0	6.9	1.4
80°	5.6	3.0	7.2	2.0	8.1	1.4
78°	6.9	3.0	8.5	2.0	9.4	1.4
75°	8.6	2.7	10.3	2.0	11.1	1.4
70°	11.4	1.7	13.1	1.55	13.8	1.37
65°	14.1	1.0	15.6	0.95	16.3	0.9
60°	16.6	0.55	18.0	0.5	18.6	0.5
A(°)	59~82					

A: ブーム角度の範囲(無負荷時)